

# Spirit™ 300, 600 & 1200

Liquid Oxygen Portables



## Comfort and Convenience

CAIRE's Spirit Liquid Oxygen Portables are designed to maximize patient comfort, convenience and ambulation. The Spirit models provide the average oxygen patient with therapy on the move for longer durations. With their light weight and comfortable, visually pleasing design, Spirits offer a new dimension of patient freedom.

All Spirit models have a built-in electronic Digital Oxygen Conserving Device (DOCD), which delivers a set pulse volume of gas with each breath. The DOCD extends oxygen duration per setting and allows the Spirit a light weight and compact design. The DOCD is powered by long-lasting dual C cell batteries, which are easy to change. The one, simple-to-use control knob is user-friendly for the patient, while the soft feature case promotes comfort and confidence.

Available in side and top fill options, the Spirits are easy to fill. The simple one step filling procedure requires no power and creates no noise.



### PRODUCT FEATURES

- Small, lightweight design allows for a more active lifestyle
- Easy portability
- Selectable flow rates from 1–5 LPM, and a continuous flow setting
- Provides between 8–30 hours of use at setting 2
- Available in side-fill or top-fill compatibility
- Comfortable soft case



CAIRE has the widest range of oxygen products available, with options available to meet each patient's prescription and mobility needs. Visit [www.caireinc.com](http://www.caireinc.com) to learn about on-demand and high-flow portable LOX units and our portable, transportable and stationary oxygen concentrators.

# Spirit™ 300, 600 & 1200

Liquid Oxygen Portables

## Product Specifications

	Spirit 300	Spirit 600	Spirit 1200
LOX Capacity	0.8 lb (0,36 kg)	1.5 lb (0,68 kg)	3.0 lb (1,36 kg)
Gaseous Equivalent Capacity	275 L	516 L	1026 L
Weight, Empty	3.5 lb (1,6 kg)	4.1 lb (1,86 kg)	5.0 lb (2,27 kg)
Weight, Filled	4.3 lb (1,95 kg)	5.6 lb (2,54 kg)	8.5 lb (3,63 kg)
Height	8.8 in. (223 mm)	11.5 in. (292 mm)	14.0 in. (355 mm)
Typical use time at Setting 2	8 hours	16.1 hours	30.4 hours
Operating Pressure	20 psi (137 kPa)	20 psi (137 kPa)	20 psi (137 kPa)
Normal Evaporation Rate	1.3 lb/ day (0,57 kg/ day)	1.3 lb/ day (0,57 kg/ day)	1.3 lb/ day (0,57 kg/ day)
Standard Flow Control Range	Demand: Off 1, 1.5, 2, 3, 4, 5 LPM, CF*	Demand: Off 1, 1.5, 2, 3, 4, 5 LPM, CF*	Demand: Off 1, 1.5, 2, 3, 4, 5 LPM, CF*

\* Continuous Flow (CF) is 2 LPM



## Ordering Information\*\*

Description	Catalog Number
Spirit 300 TF (top fill)	13104204
Spirit 300 SF (side fill)	13103130
Spirit 600 TF (top fill)	13100107
Spirit 600 SF (side fill)	13104167
Spirit 1200 TF (top fill)	11940233
Spirit 1200 SF (side fill)	11940532

## Accessories

Shoulder Strap	13234703
----------------	----------

\*\* Catalog Numbers reflect US English Part Numbers; for language-specific part numbers, please contact Customer Service.



CAIRE Contact Information:  
Providers Toll Free  
1.800.482.2473  
[www.caireinc.com](http://www.caireinc.com)

SEE PRODUCT WARRANTY STATEMENT FOR COMPLETE INFORMATION. Please consult the applicable product instructions for use for product indications, contraindications, warnings, precautions, and detailed safety information.